

## National Institute for Micro, Small and Medium Enterprises (ni-msme)

(An organization of Ministry of MSME, Govt. of India) and ISO 9001-2015 certified)
Yousufguda, Hyderabad – 500 045. Telangana, India

Sealed quotations are invited from registered contractors for the following civil work, the details of which are specified below:

"Diversion of storm water to well and rain water harvesting pits in ni-msme campus, Yousufguda, Hyderabad."

The sealed quotations shall be sent by Registered Post/Speed Post/By hand to "Administrative & Accounts Officer, ni-msme, Yousufguda, Hyderabad – 500 045 on or before 13.06.2024.

**Note:** The Director General reserves the right to cancel one or all the quotations without assigning any reasons.

### 1. The details of the work is as follows:

Name of Work	Approximate Value of work (including GST Rs.)	Period of Completion
1	2	3
"Diversion of storm water to well and rain water harvesting pits in ni-msme campus"	₹ 2,84,556/-	30 days

The tender document can be downloaded from ni-msme official website <a href="https://www.nimsme.org">www.nimsme.org</a> from "tenders" in "Announcements" menu.

#### **General Terms & Conditions:**

- Bids comprises two parts, the Technical and the Financial. Both parts must be submitted in hard copy through Registered Post/Speed Post/by hand on or before 17:00 HRS on 13.06.2024 and the 'Technical Part' of the quotations will be opened on 13.06.2024. The Financial covers will be opened after evaluation of technical bids.
- 2. The contractor shall submit copies of registration & other requisite documents along with the technical bid on or before due date of submission. Contractor should produce the original of all documents for verification if asked by the competent authority.
- 3. The contractor has to deposit Earnest Money (EMD) of Rs.5,692/- (Rupees five thousand six hundred and ninety two only) in the form of Demand Draft from Scheduled / Nationalized Bank drawn in favor of "ni-msme, payable at Hyderabad" and the DD should be submitted to this office towards EMD along with technical and financial in separate cover failing which the bid will be rejected. Bidders are requested to write their name and full address at the backside of the Demand Draft.
- 4. The contractor shall furnish the following particulars in the formats enclosed supported by documentary evidence as specified in the formats. Attested copies of documents relating to the Registration of the firm, Registration as Civil Contractor, Partnership Deed, Articles of Association, Commercial Tax/ Registration, GST, PAN Number & TAN number etc.
- Contractor should produce the originals of all the documents for verification as and when asked by the Competent Authority. In case of failure to produce all the originals the tender will not be considered and Earnest Money Deposit will be forfeited.
- 6. Contractor shall furnish declaration that they have not been blacklisted in any department in Telangana & AP. Any false declaration in this regard which come to notice at a later date will disqualify them and the tenders so received will be rejected.
- The rates quoted shall include all taxes, GST, insurance, transportation, royalty, seigniorage charges that are applicable from time to time as per statutory rules of State/ Central Govt.
- 8. The rates shall invariably be written in figure and words and amount for each item worked out and filled in the schedule/BoQ. All corrections made while filling shall be signed by the Contractor.
- 9. The tender for the work shall remain open for acceptance for a period of 30 days from the date of opening of the tenders. If any tenders withdraws his tender before the said period or issue of letter of acceptance/intent, whichever is earlier, or, makes any modifications in the terms and conditions of the tender which are not acceptable to ni-msme, then ni-msme shall without prejudice to any other right or remedy, be at liberty to forfeit 50% (fifty-percent) of the said Earnest Money as aforesaid.

- 10. Each page of tender document should be signed by the contractor with seal.
- 11. Failure to furnish documentary proof in respect of any particulars furnished by contractor in the bid form will entail rejection of the bid and forfeiture of the EMD paid. If it is noticed that any of the particulars, Bank Guarantee certificate and other documents furnished by the contractor are found false/fabricated, the contractor will be "black listed".
- 12. It is the responsibility of the contractor/tenderer to visit the site before submitting their quotation for which the contractor may contact Consultant (Engineer) at 040-23633247 on all working days i.e., Monday to Saturday from 9:00 AM to 5:30 PM.
- 13. The Director General, **ni-msme**, Hyderabad reserves the right to accept or reject any quotation(s) without assigning any reasons.
- 14. The work shall be completed within 30 days from the date of award of work.
- 15. The labour engaged and working equipment brought by the contractor for the work shall be recorded in the **ni-msme** Security Gate before entering into the premises and should obtain necessary gate pass for shifting the equipment.
- 16. Payment will be made to the contractor on submission of the bill along with statement of actual measurements taken in the presence of the Consultant (Engineer) of **ni-msme**, Hyderabad.
- 17. The Contractor is bound to execute all supplemental works that are found essential, incidental and inevitable during execution of main work.
- 18. Extra items of work shall not vitiate the contract. The contractor shall be bound to execute extra items of work as directed by the **ni-msme**. The authorities of **ni-msme** as per the conditions of contract shall work out the rates for extra items and the same are binding on the contractor.
- 19. The **ni-msme**, Hyderabad is not responsible for any damage caused to the labour/manpower engaged by the contractor during the execution of work.
- 20. Bills submitted by the contractor will be settled after certification by the Civil Works Committee of **ni-msme** with regard to its quality. Any defect in the work has to be rectified free of cost by the contractor.
- 21.**ni-msme**, Hyderabad is not responsible for payment of wages to the Manpower engaged by the contractor and statutory dues for the work at **ni-msme**, Hyderabad.
- 22. Director General, **ni-msme**, Hyderabad reserves the right to increase/decrease the quantity of work. The contractor shall have no claim to any payment of compensation or otherwise whatsoever, on account of the decrease in quantity of work or foreclosure of the whole or part of the works.

- 23. The work shall be executed as per the specifications and as directed by ni-msme authorities.
- 24.10% of the total bill amount will be withheld as Security Deposit for 12 months from the date of actual completion of the work.
- 25. The EMD will be forfeited in case the contractor does not execute the work after awarding the work.

# **Special Conditions**

### 26. Water Supply:

The Contractor has to pay for water consumed for the work on actual basis.

#### 27. Electrical Power:

In case of failure of electricity, the contractor has to make alternative arrangements for supply of electricity by Diesel Generator sets of suitable capacity at place of work. If the department arranges the supply, necessary tariff rates shall have to be paid based on the prevailing rates. The contractor will pay the bills of Electricity Department for the cost of power consumed by him.

28. The power shall be used for bonafide departmental works only.

Details of value of Civil works executed during the last three financial years by the Bidder.

SI. No.	Financial Year	Value in Rs.
1.	2020-21	
2.	2021-22	
3.	2022-23	

a) Attach certificate(s) issued by the officer not below the rank of EE concerned showing work wise / year wise values of work done in respect of all the works executed by the Bidder during last 3 financial years.

Signature of the Bidder

# **SCHEDULE OF QUANTITIES**

Name of the work :Diversion of strom water to well and rain water harvesting pits in ni-msme compound, yousufguda, Hyderabad

SI.No.	Description of Item	Quan	tity	Rate (Rs)	Unit	Amount(Rs)
1	Earth work in excavation by mechanical means (Hydraulic excavator) / manual means in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.					
a)	All kinds of soil.	61.00	Cum		One Cubic Metre	
2	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering, lead up to 50 m and lift up to 1.5 m.	12.08	Cum		One Cubic Metre	
3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level:					
a)	1:2:4 (1 cement : 2 coarse sand(zone- III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size derived from natural sources)	2.00	Cum		One Cubic Metre	
b)	1:5:10 (1 cement : 5 manufactured sand derived from Recycled Concrete Aggregate (RCA) : 10 graded stone aggregate 40 mm nominal size including Recycled Aggregate (RA))	10.00	Cum		One Cubic Metre	

4	Providing and fixing 750 X 450 X 75 precast cement concrete slabs, reinforced with 10 mm dia five nos longitudinal & 8 nos cross sectional T.M.T. Bars of grade Fe-500D or more including hoisting and setting in position with cement mortar 1:3 (1 Cement: 3 coarse sand), cost of required Centering complete with neat cement punning.			
	1:1.5:3 (1 cement : 1.5 coarse sand (zone-III) derived from natural sources : 3 graded stone aggregate 20mm nominal size derived from natural sources).	6.00	each	each
5	Half brick masonry with common burnt clay F.P.S. (non modular) bricks of class designation 35 in foundations and plinth in :			
a)	Cement mortar 1:4 (1 cement : 4 coarse sand)	141.00	Sqm	One Square Metre
6	Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion, (i) Single socketed pipes.			
	(i)Single socketed pipes.			
	110 mm diameter	12.00	m	One Running

7	Providing and fixing on wall face unplasticised - PVC moulded fittings/accessories for unplasticised Rigid PVC rain water pipes conforming to IS 13592 Type A, including jointing with seal ring conforming to IS: 5382, leaving 10 mm gap for thermal expansion.  Single tee with door					
	110x110x110 mm	6.00	Nos		One Each	
0	12 man compart plants of min.			Г		1
8 a)	12 mm cement plaster of mix : 1:6 (1 cement: 6 coarse sand)	177.00	Sqm		One Square	
aj	1.0 (1 cement. o coarse sand)	177.00	Jqiii		Metre	
9	Constructing brick masonry de-silting					
	chamber in cement mortar 1:4 ( 1 cement : 4 coarse sand ) with R.C.C.					
	top slab with 1:1.5:3 mix (1 cement :					
	1.5 coarse sand (zone-III): 3 graded stone aggregate 20 mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand (zone-III): 8					
	graded stone aggregate 40 mm nominal size), inside plastering 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with					
	floating coat of neat cement and making flooring in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating					
	coat of neat cement complete as per standard design :					
a)	Inside size 120x90 cm and 90 cm deep including Rectangular shape 600x450 mm pre cast RCC cover with frame (medium duty):					
i)	With common burnt clay F.P.S. (non modular) bricks of class designation 35	1.00	No.		Each	

Disposal of building rubbish / malba / similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.	49.00	Cum		One Cubic Metre	
Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.	1.69	Cum		One Cubic Metre	
Supplying, filling, spreading & leveling gravels of size range 5 mm to 10 mm, in the recharge pit, over the existing layer of boulders, in required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.	1.35	Cum		One Cubic Metre	
Supplying, filling, spreading & leveling coarse sand of size range 1.5 mm to 2 mm in recharge pit, in required thickness over gravel layer, for all leads& lifts, all complete as per direction of Engineer -in-charge.	0.34	Cum		One Cubic Metre	
			Total :		
	similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.  Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling gravels of size range 5 mm to 10 mm, in the recharge pit, over the existing layer of boulders, in required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling coarse sand of size range 1.5 mm to 2 mm in recharge pit, in required thickness over gravel layer, for all leads& lifts, all complete as per	similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.  Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling gravels of size range 5 mm to 10 mm, in the recharge pit, over the existing layer of boulders, in required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling coarse sand of size range 1.5 mm to 2 mm in recharge pit, in required thickness over gravel layer, for all leads& lifts, all complete as per	similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.  Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling gravels of size range 5 mm to 10 mm, in the recharge pit, over the existing layer of boulders, in required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling coarse sand of size range 1.5 mm to 2 mm in recharge pit, in required thickness over gravel layer, for all leads& lifts, all complete as per	similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.  Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling gravels of size range 5 mm to 10 mm, in the recharge pit, over the existing layer of boulders, in required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling complete as per direction of Engineer-in-charge.  O.34 Cum  Supplying, filling, spreading & leveling coarse sand of size range 1.5 mm to 2 mm in recharge pit, in required thickness over gravel layer, for all leads& lifts, all complete as per direction of Engineer-in-charge.	similar unserviceable, dismantled or waste materials by mechanical means, including loading, transporting, unloading to approved municipal dumping ground or as approved by Engineer-in-charge, beyond 50 m initial lead, for all leads including all lifts involved.  Supplying, filling, spreading & leveling stone boulders of size range 5 cm to 20 cm, in recharge pit, in the required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling gravels of size range 5 mm to 10 mm, in the recharge pit, over the existing layer of boulders, in required thickness, for all leads & lifts, all complete as per direction of Engineer-in-charge.  Supplying, filling, spreading & leveling coarse sand of size range 1.5 mm to 2 mm in recharge pit, in required thickness over gravel layer, for all leads& lifts, all complete as per direction of Engineer-in-charge.